

FIG. 1



FIG. 2

Nylon Weatherproof Cord Grips

CODE	CABLE SIZE RANGE (inches)	NPT SIZE (inches)
1399	0.197 to 0.348	1/2

Stainless Steel Square Lock Flexible Armor

CODE	I.D. (inches)	O.D. (inches)	COATING	FIG. NO.
FX188SL	3/16	0.275	None	1
FX125SL	1/8	0.207	None	1
FX250SL	1/4	0.345	None	1
FX188SLP	3/16	0.328	PVC (black)	2
FX188SLF	3/16	0.313	FEP (white)	2




FIG. 3




FIG. 4

Holding Fixtures for Silicon Carbide Tubes

CODE	DESCRIPTION	FIG. NO.
<i>18J SERIES TUBES</i>		
370006	3/4" NPT x 1(7/8)" I.D.	3
<i>18JC SERIES TUBES</i>		
370007	Support casting with flange	4




FIG. 6



FIG. 7

Coil Cords



CODE	DESCRIPTION	RETRACTED LENGTH (inches)	EXTENDED LENGTH (inches)
[1]32060-0	Polyurethane outer, PVC inner, 2 free ends,stripped	12	60
[1]32120-0	Polyurethane outer, PVC inner, 2 free ends,stripped	24	120
RTD32060-0	Polyurethane outer, PVC inner, 3 conductor with 2 free ends,stripped	12	60

[1] Insert calibration code: J, K, T, E, R, S, U
Consult factory for availability of other lengths

Miscellaneous Items

CODE	DESCRIPTION	FIG. NO.
440017	3/4 oz. silicone rubber head sealant (RTV)	
440040	10cc heat transfer compound (300 °F max)	
6EB - DC	3/4" x 1/2" reducing face bushing	6
710	1/2" box connector	7