

ORDER CODES

Unconfigured Order Number: 441-00^[1]**Example Configured Order Number:****4 4 1**

-

1 J U

-

S (50-300) F**1**

CODE	DESCRIPTION
1	Thermocouple (TC)
2	RTD (2-wire)
3	RTD (3-wire)
4	RTD (4-wire)

2

CODE	DESCRIPTION
J	Type J thermocouple
K	Type K thermocouple
T	Type T thermocouple
N	Type N thermocouple
E	Type E thermocouple
R	Type R thermocouple
S	Type S thermocouple
B	Type B thermocouple
85	100 ohm platinum ($\alpha = 0.00385\text{ }^{\circ}\text{C}^{-1}$)
55	500 ohm platinum ($\alpha = 0.00385\text{ }^{\circ}\text{C}^{-1}$)
95	1000 ohm platinum ($\alpha = 0.00385\text{ }^{\circ}\text{C}^{-1}$)
MV	Millivolts
W	Resistance

3

CODE	DESCRIPTION
U	Upscale Burnout $\geq 21.0\text{ mA}$
D	Downscale Burnout $\leq 3.5\text{ mA}$

4

RANGE
S (lower limit – upper limit)

5

CODE	DESCRIPTION
C	Celsius
F	Fahrenheit

Accessories

CODE	DESCRIPTION
10303	Communication cable and software (USB)
10307	35 mm DIN-rail mounting clip

[1] Default setting for unconfigured transmitter is 3-wire Pt100 (0 - 100) °C.