

## ACCURACY (continued)

## Physical input range of the sensors

TYPE	MEASUREMENT ACCURACY <sup>[1]</sup>
(10 to 400) Ω	Cu10, Cu50, Cu100, polynomial RTD, Pt50, Pt100, Ni100, Ni120
(10 to 2000) Ω	Pt200, Pt500, Pt1000, Ni1000
(-20 to 100) mV	Thermocouple type: C, D, E, J, K, L, N
(-5 to 30) mV	Thermocouple type: B, R, S, T, U

[1] % is related to the adjusted measurement range (the value to be applied is the greater)

## General

Repeatability	0.03% of the physical input range (15 Bit) Resolution A/D conversion: 18 Bit
Load influence	≤ ± 0.005%/V deviation from 24 V, related to the full-scale value
Long term stability	≤ 0.1 °C [0.18 °F] / year or ≤ 0.05%/year Data under reference conditions. % relates to the set span. The larger value applies.

## Temperature Drift

Total temperature drift = input temperature drift + output temperature drift	Effect on the accuracy when ambient temperature changes by 1 °C [1.8 °F]	
	Input (10 to 400) Ω	0.002% of measured value
	Input (10 to 2000) Ω	0.002% of measured value
	Input (-20 to 100) mV	typ. 0.002% of measured value (maximum value = 1.5 x typical)
	Input (5 to 30) mV	typ. 0.002% of measured value (maximum value = 1.5 x typical)
	Output (4 to 20) mA	typ. 0.002% of measured value (maximum value = 1.5 x typical)

## INSTALLATION CONDITIONS

## Ambient Conditions

Ambient temperature	Without display: (-40 to 85) °C [-40 to 185] °F With display: (-40 to 70) °C [-40 to 158] °F NOTE: The display can react slowly for temperature < -20 °C [< -4 °F]
Storage temperature	Without display: (-40 to 100) °C [-40 to 212] °F With display: (-40 to 85) °C [-40 to 185] °F
Allowable Altitude	6500 ft. above sea level
Climatic class	As per EN 60 654-1, Class C
Moisture condensation	Allowable
Shock and vibration protection	3 g / (2 to 150) Hz according to IEC 60 068-2-6
EMC immunity	Interference immunity and interference emission as per EN 61 326-1 (IEC 1326) (0.08 to 2) GHz 10 V/m; (1.4 to 2) GHz 30 V/m to EN 61 000-4-3
Protection	IP67, NEMA 4X, Class 1, Division 1, Group A, B, C; Class II Division I, Groups E, F, G and Class III, Division I (when specified)

HART® is a registered trademark of HART Communication Foundation