

1/32	0.015625	33/64	0.515625
1/16	0.03125	17/32	0.53125
3/32	0.046875	35/64	0.546875
1/8	0.0625	9/16	0.5625
5/32	0.078125	37/64	0.578125
3/16	0.09375	19/32	0.59375
7/32	0.109375	39/64	0.609375
1/4	0.125	5/8	0.625
9/32	0.140625	41/64	0.640625
5/16	0.15625	21/32	0.65625
11/32	0.171875	43/64	0.671875
3/8	0.1875	11/16	0.6875
7/16	0.203125	45/64	0.703125
1/2	0.21875	23/32	0.71875
5/8	0.234375	47/64	0.734375
3/4	0.25	3/4	0.75
7/8	0.265625	49/64	0.765625
1	0.28125	25/32	0.78125
	0.296875	51/64	0.796875
	0.3125	13/16	0.8125
	0.328125	53/64	0.828125
	0.34375	27/32	0.84375
	0.359375	55/64	0.859375
	0.375	7/8	0.875
	0.390625	57/64	0.890625
	0.40625	29/32	0.90625
	0.421875	59/64	0.921875
	0.4375	15/16	0.9375
	0.453125	61/64	0.953125
	0.46875	31/32	0.96875
	0.484375	63/64	0.984375
	0.5	1	1

INCHES in DECIMALS of a FOOT

1/16 - 0.0052	1 - 0.0833
3/32 - 0.0078	2 - 0.1667
1/8 - 0.0104	3 - 0.2500
3/16 - 0.0156	4 - 0.3333
1/4 - 0.0208	5 - 0.4167
5/16 - 0.0260	6 - 0.5000
3/8 - 0.0313	7 - 0.5833
1/2 - 0.0417	8 - 0.6667
5/8 - 0.0521	9 - 0.7500
3/4 - 0.0625	10 - 0.8333
7/8 - 0.0729	11 - 0.9167

Standard Wire Gauges in Approximate Decimals of an Inch and mm.

WIRE GAUGE	AMERICAN or BROWN AND SHARP DIAMETER (inches)	DIAMETER MILLIMETERS	BIRMINGHAM or STUBS	US STANDARD
1	0.2893	7.348	0.300	0.281
2	0.2576	6.544	0.284	0.266
3	0.2294	5.827	0.259	0.250
4	0.2043	5.189	0.238	0.234
5	0.1819	4.621	0.220	0.219
6	0.1620	4.115	0.203	0.203
7	0.1443	3.665	0.180	0.188
8	0.1285	3.264	0.165	0.172
9	0.1144	2.906	0.148	0.156
10	0.1019	2.588	0.134	0.141
11	0.0907	2.304	0.120	0.125
12	0.0808	2.053	0.109	0.109
13	0.0720	1.829	0.095	0.0938
14	0.0641	1.628	0.083	0.0781
15	0.0571	1.450	0.072	0.0703
16	0.0508	1.291	0.065	0.0625
17	0.0453	1.150	0.058	0.0563
18	0.0403	1.024	0.049	0.0500
19	0.0359	0.9116	0.042	0.0438
20	0.0320	0.8118	0.035	0.0375
21	0.0285	0.7230	0.032	0.0344
22	0.0253	0.6438	0.028	0.0313
23	0.0226	0.5733	0.025	0.0281
24	0.0201	0.5106	0.022	0.0250
25	0.0179	0.4547	0.020	0.0219
26	0.0159	0.4049	0.018	0.0188
27	0.0142	0.3606	0.016	0.0172
28	0.0126	0.3211	0.014	0.0156
29	0.0113	0.2859	0.013	0.0141
30	0.0100	0.2546	0.012	0.0125
31	0.0089	0.2268	0.010	0.0109
32	0.0080	0.2019	0.009	0.0102
33	0.00708	0.178	0.008	0.0094
34	0.00630	0.152	0.007	0.0086
35	0.00561	0.138	0.005	0.0078
36	0.00500	0.127	0.004	0.0070
37	0.00445	0.1131		0.0066
38	0.00397	0.1007		0.0063
39	0.00353	0.08969		
40	0.00314	0.07987		

CONDUIT SIZE (I.P.S.)	Approximate No. of Insulated Double Conductor Lengths of Extension					
	Wire - Size Conductor					
	NO. 14	NO. 14 ^[1]	NO. 16	NO. 16 ^[2]	NO. 20	NO. 24
1/2"	1	2	2	1	7	9
3/4"	3	7	4	2	16	21
1"	5	10	6	4	24	29
1 1/4"	7	14	10	5	35	44
1 1/2"	13	23	13	7	48	69
2"	18	48	20	11	73	95

[1] Single Conductor Insulated

[2] Three Conductor Insulated